

Series 110 Omni-Valve

OV-110 Ordering Information

Model: OV-110 - _____ - _____ - _____ - _____ - _____ - _____ - _____ - _____ - IS

MAXIMUM CAPACITY

1. 500 ppd (10 kg/hr)
2. 2000 ppd (40 kg/hr)
3. 6000 ppd (120 kg/hr)

GAS OR LIQUID

- A. Ammonia (NH₃)
 - B. Sodium Bisulfite (NaHSO₃)
 - C. Chlorine (Cl₂)
 - S. Sulfur Dioxide (SO₂)
 - H. Sodium Hypochlorite (NaOCl)
- Other:** Consult Factory

RANGE

- | | |
|-----------------------|--------------------------|
| 1. 10 ppd (200 gr/hr) | 7. 1000 ppd (20 kg/hr) |
| 2. 25 ppd (500 gr/hr) | 8. 2000 ppd (40 kg/hr) |
| 3. 50 ppd (1 kg/hr) | 9. 3000 ppd (60 kg/hr) |
| 4. 100 ppd (2 kg/hr) | 10. 4000 ppd (80 kg/hr) |
| 5. 250 ppd (5 kg/hr) | 11. 6000 ppd (120 kg/hr) |
| 6. 500 ppd (10 kg/hr) | |

Note: For liquid use please specify the desired max capacity.

POWER REQUIREMENTS

1. 120V 60Hz
2. 240V 50Hz

CONTROL CONFIGURATION

- | | |
|-----------------------------|----------------------------|
| 1. Flow Pacing | 5. Compound Loop (ORP) |
| 2. Residual | 6. Step Feed |
| 3. ORP | 7. Dual Input Feed Forward |
| 4. Compound Loop (Residual) | 8. Dual Set Point |

POWER CABLE LENGTH

1. 6 feet (1.5 m) standard
2. Other (consult factory)

SIGNAL CABLE LENGTH

1. 25 feet (8 m) per input channel
2. Specify length required

POWER LINE ISOLATOR

1. None (standard)
2. Included

Capacity Ranges	
Gas Feed	10, 25, 50, 100, 250, 500, 1000, 2000, 3000, 4000, & 6000 PPD
Liquid Feed	4 GPH through 10 GPM



INSTRUMENTS

